

Fine Clarifier
Levasil® BF30 (BEVASIL 30)

Levasil BF30 silica sol fining agent is a special silica sol of exceptional purity and activity for the fining of beverages. It is used in combination with gelatin or other positively charged fining agents as flocculating intensifier. Levasil BF30 silica sol fining agent contains 30% technically pure colloid silicon dioxide.

Application

The beverage treatment with Levasil BF30 silica sol fining agent and SIHA® Gelatin results in an economical and taste neutral clarification. A taste improvement is also often attained. Even in difficult cases, the clarification of the beverage is accelerated; the turbidity deposit becomes more compact, and beverage losses, filtration time, and the use of filtering agents are reduced.

Application quantities

To ascertain the optimum relation between Levasil BF30 silica sol fining agent and SIHA Gelatin fining agent, tests should be carried out in a 3.38 fl oz (100 ml) scale. To achieve exact and practical results, the sample should be kept at cellar temperature during the entire test.

Tannin and colloid content, pH value, viscosity and particle characteristics are further influential factors during clarification. The time available for reaction and flocculation of the fine clarification are of essential importance. These important factors determine the application quantities of the individual clarification agents. The Levasil BF30 silica sol fining agent - SIHA Gelatin proportions and quantities in the table may be taken as standard values.

Standard application

64 fl oz/1,000 gal (50 ml/hl) Levasil BF30
 + 6.68 lb/1,000 gal (5 g/hl) SIHA Gelatin Fine Granules
 or

64 fl oz/1,000 gal (50 ml/hl) Levasil BF30
 + 64 fl oz/1,000 gal (50 ml/hl) SIHA Gelatin Liquid

Fining process

Levasil BF30 silica sol fining agent and SIHA Gelatin must be added separately and upon each addition be thoroughly mixed. Neither of these fining agents may ever be added in succession without prior mixing to the beverage to be fined. Before adding the fining agent, the contents of the batch should be intensively stirred by means of an effective motor mixer.

Application	Levasil BF30 fl oz/100 gal (ml)	Gelatin Fine Granules lb/1,000 gal (g/hl)	SIHA Gelatin Liquid fl oz/100 gal (ml/hl)
Wine clarification	3.84 – 7.68 (30 – 60)	0.13 – 0.42 (1.5 – 5.0)	3.2 -6.4 (25 – 50)
Wines which are difficult to clarify	6.4 – 12.8 (50 – 100)	0.42 – 0.83 (5.0 – 10.0)	6.4 – 12.8 (50 – 100)
Apple juice, products which are difficult to clarify	6.4 – 12.8 (50 – 100)	0.83 (10) and more	6.4 – 12.8 (50 – 100)
Beverages of high tannin content used in conjunction with bentonite	6.4 (50)	0.42 – 0.83 (5.0 – 10.0)	6.4 (50)
Musts, vinegar, beverages which are difficult to clarify	12.8 (100)	0.21 – 0.42 (2.5 – 5.0)	12.8 (100)

A substantially better mixture is given by adding the fining agent continually in the liquid stream when transposing the beverage i.e. with a fining agent application device. Prior to dissolving of the fining agent with water or the beverage is recommended to improve distribution.

SIHA Gelatin Liquid fining agent may be directly added to the beverage. Here again prior to dissolving with water or the beverage is recommended for better distribution. SIHA Gelatin Fine Granules fining agent must always swell in cold water first and be dissolved at a temperature of 104 – 122 °F (40 – 50°C). Please observe the notes in our Technical Data Sheet to SIHA Gelatin fining agent.

Product Characteristics

Levasil BF30 silica sol fining agent is a transparent, slightly opalescent aqueous silicic acid solution and contains 30% colloid silicon dioxide (SiO₂). The possibility of using the water insoluble, amorphous silicon dioxide as "aqueous solution" is achieved by colloid distribution.

The principle of clarification and fining with Levasil BF30 silica sol fining agent and SIHA Gelatin fining agent arises from the reciprocal flocculation of negative charged silica sol and positive charged gelatin. The clarification fining is therefore just as effective at low cellar temperatures as in heat fining of fruit juices or red sweet reserves.

Safety

No negative effects are known when used in line with the recommendations and upon professional processing of Levasil BF30 silica sol fining agent.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

Levasil BF30 silica sol fining agent is produced and packed with the utmost care and is stored in odor free polyethylene drums.

Open packages should be used up as soon as possible.

Levasil BF30 is sensitive to frost. Do not store and/or transport below 41 °F (5 °C).

Delivery Information

Levasil BF30 silica sol fining agent is sold under article no. 62.103 and is available in the following package sizes:

2.2 lb (1 kg)	PE bottle
13.23 lb (6 kg)	PE can
55.12 lb (25 kg)	PE can
308.6 lb (140 kg)	PE drum
2,756 lb (1,250 kg)	IBC Container

Certified Quality

Levasil BF30 silica sol fining agent is regularly monitored during the production process to ensure consistent high product quality. This comprises the technical function criteria just as it does the legal requirements governing the safe use for nutrition. Strict controls are undertaken before and during final packaging.

Levasil® is a registered trademark of Akzo Nobel Chemicals GmbH.

Nordamerika

44 Apple Street
Tinton Falls, NJ 07724
Gebührenfrei: 800 656-3344
(nur innerhalb Nordamerikas)
Tel: +1 732 212-4700

China

No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Europa/Afrika/Naher Osten

Auf der Heide 2
53947 Nettersheim, Deutschland
Tel: +49 2486 809-0

Singapur

4 Loyang Lane #04-01/02
Singapur 508914
Tel: +65 6825-1668

Friedensstraße 41
68804 Altlußheim, Deutschland
Tel: +49 6205 2094-0

Brasilien

Av. Julia Gaioli, 474 – Bonsucesso
07251-500 – Guarulhos, Brasilien
Tel: +55 11 2465-8822

An den Nahewiesen 24
55450 Langenlonsheim, Deutschland
Tel: +49 6704 204-0

Für weitere Informationen kontaktieren Sie uns per E-Mail unter filtration@eaton.com oder online unter eaton.com/filtration

EN
1 B 4.4.4
06-2016

© 2015 Eaton. Alle Rechte vorbehalten. Sämtliche Handelsmarken und eingetragenen Warenzeichen sind Eigentum der jeweiligen Unternehmen. Sämtliche in diesem Prospekt enthaltenen Informationen und Empfehlungen hinsichtlich der Verwendung der hierin beschriebenen Produkte basieren auf Prüfungen, die als zuverlässig angesehen werden. Dennoch obliegt es der Verantwortung des Benutzers, die Eignung dieser Produkte für seine eigene Anwendung festzustellen. Da die konkrete Verwendung durch Dritte außerhalb unseres Einflussbereiches liegt, übernimmt Eaton keinerlei ausdrückliche oder stillschweigende Gewährleistung für die Auswirkungen einer solchen Verwendung oder die dadurch erzielbaren Ergebnisse. Eaton übernimmt keinerlei Haftung in Zusammenhang mit der Verwendung dieser Produkte durch Dritte. Die hierin enthaltenen Informationen sind nicht als absolut vollständig anzusehen, da weitere Informationen notwendig oder wünschenswert sein können, falls spezifische oder außergewöhnliche Umstände vorliegen, beziehungsweise aufgrund von geltenden Gesetzen oder behördlichen Bestimmungen.



Powering Business Worldwide