Technical Information

Deacidification Potassium Bicarbonate



Potassium Bicarbonate stabilizer from Eaton's Begerow Product Line is formulated for quick, polishing deacidification of musts and young wines. Current legislation must always be observed.

The specific advantages of Potassium Bicarbonate stabilizer:

- Enables particularly quick and complete deacidification if combined with a subsequent cold treatment
- For reduction of 8.35 lb/1,000 gal (100 g/hl) tartaric acid, 5.57 lb/1,000 gal (66.7 g/hl)
 Potassium Bicarbonate stabilizer are required

Product Description

Tartaric acid in must and wine is deposited as cream of tartar (potassium hydrogen tartrate) using Potassium Bicarbonate stabilizer. The special advantage of deacidification using Potassium Bicarbonate stabilizer is the possibility of performing polishing deacidification of the wine shortly before bottling. After deacidification, the wine has to be put into cold storage for 2 to 3 weeks to make sure that the cream of tartar is safely deposited. If the wine is stored at cellar temperature precipitation may take several weeks.

Application

To remove 8.35 lb/1,000 gal (100 g/hl) = $1^{\circ}/_{\circ o}$ tartaric acid, 5.57 lb/1,000 gal (66.7 g) Potassium Bicarbonate stabilizer are required per 26.42 gal (100 l) must or wine. It is added directly to the wine in powder form while mixing vigorously. It can also be pre-mixed to a paste in liquid. The release of CO₂ may cause extensive foam formation, therefore the deacidifying vessel must have enough head space above the liquid.

At normal cellar temperatures the cream of tartar will deposit within several weeks. If the deacidified must or wine is needed quicker it must be put into cold storage for several days.

Please note that the calculated final acid content will not be found until the cream of tartar has deposited completely. Before that an acid analysis will show a lower level of deacidification than calculated. In this case, the acid has already been neutralized but the tartaric acid is still in the beverage.

It still has to be deposited as cream of tartar. Storage of the wine should be continued until the wine cream of tartar has completely precipitated.

Safety

When used as directed no negative effects are known.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

Store in a dry and well-ventilated place.

Delivery Information

Potassium Bicarbonate stabilizer is sold under article no. 63.305 and is available in the following package sizes:

11.02 lb (5 kg) plastic bucket

Potassium Bicarbonate stabilizer is sold under article no. HW.014 and is available in the following package size:

55.1 lb (25 kg) PE sack
HS Customs Tariff: 2836 40 00

Certified Quality

Potassium Bicarbonate stabilizer is monitored regularly during the production process to ensure consistently high quality. These inspections cover technical function criteria as well as compliance with the law governing the production and sale of foodstuffs. Strict controls are also carried out immediately before and during final packing.





North America - HQ

44 Apple Street, Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America Only) Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2 53947 Nettersheim, Germany Voice: +49 2486 809-0

Internormen Product Line Friedensstraße 41 68804 Altlussheim, Germany Voice: +49 6205 2094-0

Begerow Product Line An den Nahewiesen 24

55450 Langenlonsheim, Germany

Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso 07251-500 - Guarulhos Brazil

Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road, Changning District, Shanghai 200335, China Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02 Singapore 508914 Voice: +65 6825 1668 property of their

at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

For more information, please e-mail us

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton Filtration office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

