## Technical Information

# Beer Clarification BECOSOL TM 30

# BECO

# Silica Sol

BECOSOL 30 silica sol fining agent from Eaton's Begerow Product Line is a silica sol formulated especially for clarifying beer and improving filtration in the brewing industry. The specific surface of BECOSOL 30 silica sol fining agent guarantees optimum adsorption of substances contained in the beer that cause turbidity and at the same time has excellent flocculation properties. This gives a low and compact sediment and optimum clarification of the beer. BECOSOL 30 silica sol fining agent has a very high chemical purity and contains 30% pure colloidal silicon dioxide.

The specific advantages of BECOSOL 30 silica sol fining agent:

- Adsorption of substances contained in the beer that cause turbidity
- Optimum clarification of the treated beer
- Improved filtration properties of the beer
- Small and compact sediment

# **Application**

The effect of BECOSOL 30 silica sol fining agent in beer is based on the flocculation properties of the SiO<sub>2</sub> particles and the formation of a hydrogel. The hydrogel flocculates together with the turbidities in the beer and with a part of the protein contained in the beer that is sensitive to cold.

When the silica sol is added to the storage tank the turbidities precipitate by the force of gravity and form a compact sediment at the bottom of the tank.

Adding BECOSOL 30 silica sol fining agent to reduce turbidities in the unfiltered beer greatly improves filtration performance and prolongs the filter lifetime.

#### Dosage

Application	Quantities fl oz/100 gal (ml/hl)
Addition to hot starting wort	3.8-7.6 (30-60)
Addition to storage	4.4-5.8 (35-45)
Addition before filtration (with buffer tank)	1.3- 1.9 (10- 15)

The optimum quantity and point at which to add BECOSOL 30 silica sol fining agent should be determined individually by means of laboratory or field tests.

#### Addition to the hot starting wort

BECOSOL 30 silica sol fining agent can be added to the starting wort in three ways:

- 1. Directly to the wort copper after completion of the boiling process
- 2. To the wort line by means of a suitable measuring apparatus
- 3. Directly upon entering the whirlpool

### Addition to the storage tank

In this case, BECOSOL 30 silica sol fining agent is added directly by means of a measuring apparatus when the beer is repumped into the storage tank. For best results, the beer should already have a very low temperature (approx.  $32-41\,^\circ\text{F}\,(0-5\,^\circ\text{C})$ ) because the substances that are sensitive to cold will have already precipitated to a large extent. Thorough mixing of the beer with the silica sol must be ensured. A dosage of 5 fl oz/100 gal (40 ml/hl) sol will cause rapid clarification of the beer during storage and greatly improve its filtration properties.

# Addition before filtration

If, despite the application of finest filter aids, the beer is not filtered clearly, silica sol should be added in a buffer tank by means of a measuring apparatus before diatomaceous earth (DE) filtration. The silica sol must be added early enough so that the agglomerates can grow to a size which builds a sediment in the buffer tank until filtration. It must be guaranteed that no sediment comes to DE filtration, so that the filtration will not be unnecessarily loaded. A dosage of 1.3 to 1.9 fl oz/100 gal (10 – 15 ml/hl) is necessary.





#### **Product Characteristics**

BECOSOL 30 silica sol fining agent is a transparent, slightly opalescent solution of silicic acid in water and contains 30% silicon dioxide (SiO<sub>2</sub>).

#### Safety

When used properly no negative effects are known.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

#### Storage

BECOSOL 30 silica sol fining agent is produced and packed with utmost care and is stored in scentless polyethylene packing drums until delivery. Opened packages should be used up as soon as possible.

BECOSOL 30 silica sol is sensitive to frost. Do not store under 41 °F (5 °C).

Even a brief lowering of the temperature under 41 °F (5 °C) will lead to flocculation of the silica sol and it will become ineffective.

#### **Delivery Information**

BECOSOL 30 silica sol fining agent is sold under article no. 62.111 and is supplied in the following package sizes:

551.15 lb (250 kg) PE drum

2645.5 lb (1200 kg) IBC container on request

HS Customs Tariff: 3824 99 96

## North America - HQ

44 Apple Street, Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America Only) Voice: +1 732 212-4700

#### **Europe/Africa/Middle East**

Auf der Heide 2 53947 Nettersheim, Germany Voice: +49 2486 809-0

Internormen Product Line Friedensstraße 41 68804 Altlussheim, Germany Voice: +49 6205 2094-0

Begerow Product Line An den Nahewiesen 24 55450 Langenlonsheim, Germany

Voice: +49 6704 204-0

The product is monitored regularly in the laboratory to ensure consistently high quality.

**Certified Quality** 

#### For more information, please e-mail us at Av. Julia Gaioli, 474 - Bonsucesso filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of

Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local

> © 2012 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

Eaton office to determine availability.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

### **Brazil**

07251-500 - Guarulhos

Brazil

Voice: +55 11 2465 8822

# China

No. 7 Lane 280 Linhong Road, Changning District, Shanghai 200335, China Voice: +86 21 5200 0422

## **Singapore**

4 Loyang Lane #04-01/02 Singapore 508914 Voice: +65 6825 1668

