

## Beer Stabilization BECOSORB® 6000



### Silica Gel

**BECOSORB 6000 silica gel from Eaton's Begerow Product Line is a silicic acid-hydrogel with an average moisture content of 55%. The defined particle size of BECOSORB 6000 silica gel is formulated especially for beer filtration. Uniform surface structure and pore size together with optimum pore volume guarantee that protein compounds of high molecular weight, which might otherwise give rise to colloidal haze, are adsorbed from the beer.**

The specific advantages of BECOSORB 6000 silica gel:

- Selective adsorption of protein fractions of high molecular weight
- No influence on components of low molecular weight that are positive for foam formation
- As a hydrogel, virtually dust free handling
- Acts also as filter media, supports the filtration process
- Can be combined with PVPP and diatomaceous earth products
- Neutral flavor and aroma, chemically inert
- Free from contaminants that would spoil the beer

### Application

BECOSORB 6000 silica gel can be used safely for all stabilization processes commonly used in breweries:

1. Application during the sedimentation process
  - When transferring beer from fermentation (cellar) to stabilizing aging tanks
  - When transferring beer from a stabilizing aging tank to another tank
2. Contact method during continuous beer flow
  - When added into the dosing apparatus together with diatomaceous earth (pre-coat filtration)
  - Addition via dosing apparatus in a stabilization tank (advantage: longer contact time).
  - When added into the beer flow directly at the beer blending equipment

### Dosage

Desired shelf life of the beer and on

- the fermentation process/pH gradient,
- the oxygen content and turbidity values of the beer,
- the temperature during aging and filtration.

The average dosage is between 0.3 – 1.2 lb/100 gal (40 – 140 g/hl) beer, depending on the protein composition and the desired degree of beer stability.

The following amounts have proven useful in practice:

0.3 – 0.5 lb/100 gal (40 – 60 g/hl)	for a stability of approx. 3 – 4 months
0.5 – 0.7 lb/100 gal (60 – 80 g/hl)	for a stability of approx. 4 – 6 months
0.7 – 1.2 lb/100 gal (80 – 140 g/hl)	for a stability of approx. 6 – 12 months

To improve the stability results it is recommended that 1 lb/100 ft<sup>2</sup> (50 g/m<sup>2</sup>) BECOSORB 6000 silica gel are given in the 2<sup>nd</sup> pre-coat filtration process stage.

### Product Characteristics

With its defined particle size, uniform surface structure as pore size and pore volume BECOSORB 6000 silica gel is designed for selective adsorption of proteins of medium and high molecular weight. It has no effect on the protein components of low molecular weight that are important for foam stabilization.

Thanks to its favorable Darcy figures\*) (corresponding to a medium diatomaceous earth quality) BECOSORB 6000 silica gel also acts partially as filter media in vessel filters with high throughput volumes.

The absence of a swelling effect reduces beer losses. As a hydrated product, BECOSORB 6000 silica gel forms extremely little dust during handling and is very convenient to use. Proper application of BECOSORB 6000 silica gel guarantees maximum efficiency and economy.

### Safety

When used properly no negative effects are known. If dust forms, use an extractor or wear a breathing mask.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

## Storage

BECOSORB 6000 silica gel can adsorb moisture and odors. Therefore, it should always be stored well packed in an intact bag in a dry, well-ventilated place that is free from foreign odors.

The material must be stored and transported in the original packaging and protected from moisture and external odors.

The product should not be subject to extreme fluctuations in temperature. If possible, the product should be stored cool (optimum storage temperature is between 44.6 and 68 °F (7 – 20 °C)) and protected from direct sunlight. Condensation under the stretch film caused by large temperature changes or by the effect of the sun should be avoided.

Opened bags should be re-sealed to protect them from moisture (e.g. place into PE bags) and stored according to the above instructions.

## Delivery Information

BECOSORB 6000 silica gel is sold under article no. 62.560 and is supplied in the following package size:

45.1 lb (25 kg) valve PE bag

HS Customs Tariff: 2811 22 00

## Certified Quality

BECOSORB 6000 silica gel is monitored constantly in the laboratory to ensure consistently high quality.

*\*) Darcy is the standardized unit of measure for the permeability of a porous bed for liquids.*

### North America - HQ

44 Apple Street,  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America Only)  
Voice: +1 732 212-4700

### Europe/Africa/Middle East

Auf der Heide 2  
53947 Nettersheim, Germany  
Voice: +49 2486 809-0

### Internormen Product Line

Friedensstraße 41  
68804 Altlussheim, Germany  
Voice: +49 6205 2094-0

### Begerow Product Line

An den Nahewiesen 24  
55450 Langenlonsheim, Germany  
Voice: +49 6704 204-0

### Brazil

Av. Julia Gaioli, 474 - Bonsucesso  
07251-500 - Guarulhos  
Brazil  
Voice: +55 11 2465 8822

### China

No. 7 Lane 280 Linhong Road,  
Changning District,  
Shanghai 200335, China  
Voice: +86 21 5200 0422

### Singapore

4 Loyang Lane #04-01/02  
Singapore 508914  
Voice: +65 6825 1668

For more information, please e-mail us at [filtration@eaton.com](mailto:filtration@eaton.com) or visit us online at [eaton.com/filtration](http://eaton.com/filtration) for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton office to determine availability.

© 2012 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.